1. Identification

Product identifier American Safety Technologies MS-11CZ Buff - Part A

Other means of identification

SKU# MS709R

Recommended use Not available.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ITW Engineered Polymers
Address 130 Commerce Drive
Montgomeryville, PA 18936

United States

Telephone Customer Service 215-855-8450

Website www.itwengineeredpolymers.com

E-mail orders.na@itwep.com
Contact person EHS Department

Emergency phone number CHEMTREC 800-424-9300 International 703-527-3887

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 3Health hazardsSkin corrosion/irritationCategory 2Serious eye damage/eye irritationCategory 2Sensitization, skinCategory 1

Environmental hazards Hazardous to the aquatic environment,

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Flammable liquid and vapor. Causes skin irritation. May cause an allergic skin reaction. Causes

serious eye irritation. Toxic to aquatic life with long lasting effects.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly

closed. Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Avoid release to

Category 2

the environment. Wear protective gloves/eye protection/face protection.

Response If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before

reuse. In case of fire: Use appropriate media to extinguish. Collect spillage.

Storage Store in a well-ventilated place. Keep cool.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information

93.75% of the mixture consists of component(s) of unknown acute oral toxicity. 93.75% of the mixture consists of component(s) of unknown acute dermal toxicity. 48.56% of the mixture consists of component(s) of unknown acute inhalation toxicity. 78.51% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 49.03% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|--|--------------------------|------------|---------|
| Epoxy Resin:reaction Product Of Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin) | | 25068-38-6 | 10 - 30 |
| Nepheline Syenite | | 37244-96-5 | 10 - 30 |
| Talc | | 14807-96-6 | 7 - 13 |
| Barium Sulfate | | 7727-43-7 | 5 - 10 |
| Titanium Dioxide | | 13463-67-7 | 5 - 10 |
| Zinc Phosphate | | 7779-90-0 | 5 - 10 |
| 1-methoxy-2-propanol | | 107-98-2 | 1 - < 3 |
| Aromatic Hydrocarbon Solvents | | 64742-95-6 | 1 - < 3 |
| Carbon Black | | 1333-86-4 | 0.1 - 1 |
| Ethyl Benzene | | 100-41-4 | 0.1 - 1 |
| Other components below reportable | levels | | 10 - 30 |

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

| Inhalation | Move to fresh air. Call a physician if symptoms develop or persist. |
|------------|---|
| | |

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur. Ingestion

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the General information material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from

the chemical

Special protective equipment

and precautions for firefighters

Fire fighting equipment/instructions

Specific methods General fire hazards Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source

of ignition and flash back. During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

| US. OSHA Table Z-1 Limits for Air C Components | Туре | Value | Form |
|---|------|-----------|----------------------|
| Aromatic Hydrocarbon Solvents (CAS 64742-95-6) | PEL | 400 mg/m3 | |
| , | | 100 ppm | |
| Barium Sulfate (CAS 7727-43-7) | PEL | 5 mg/m3 | Respirable fraction. |
| , | | 15 mg/m3 | Total dust. |
| Carbon Black (CAS 1333-86-4) | PEL | 3.5 mg/m3 | |
| Ethyl Benzene (CAS 100-41-4) | PEL | 435 mg/m3 | |
| , | | 100 ppm | |
| Titanium Dioxide (CAS 13463-67-7) | PEL | 15 mg/m3 | Total dust. |
| US. OSHA Table Z-3 (29 CFR 1910.1 | 000) | | |
| Components | Туре | Value | Form |
| Barium Sulfate (CAS 7727-43-7) | TWA | 5 mg/m3 | Respirable fraction |
| • | | 15 mg/m3 | Total dust. |
| | | 50 mppcf | Total dust. |
| | | 15 mppcf | Respirable fraction. |

| Components | Туре | | V | alue | Form |
|--|---------------------|----------------------|---------------------|--------------------|----------------------|
| Talc (CAS 14807-96-6) | TWA | | 0. | 3 mg/m3 | Total dust. |
| | | | 0. | 1 mg/m3 | Respirable. |
| | | | 20 |) mppcf | |
| | | | 2. | 4 mppcf | Respirable. |
| Titanium Dioxide (CAS 13463-67-7) | TWA | | 5 | mg/m3 | Respirable fraction. |
| | | | 15 | 5 mg/m3 | Total dust. |
| | | | 50 |) mppcf | Total dust. |
| | | | 15 | 5 mppcf | Respirable fraction. |
| US. ACGIH Threshold Lin | nit Values | | | | |
| Components | Туре | | V | alue | Form |
| 1-methoxy-2-propanol (CA | S STEL | | 1(| 00 ppm | |
| 107-98-2) | T14/A | | E/ | 2 | |
| Davissa Cultata (CAC | TWA | | |) ppm | Inhalable fraction. |
| Barium Sulfate (CAS 7727-43-7) | TWA | | 5 | mg/m3 | innalable fraction. |
| Carbon Black (CAS | TWA | | 3 | mg/m3 | Inhalable fraction. |
| 1333-86-4) | | | _ | 3 | |
| Ethyl Benzene (CAS | TWA | | 20 |) ppm | |
| 100-41-4) | T14/4 | | | / 0 | D : 11 (): |
| Talc (CAS 14807-96-6) | TWA | | | mg/m3 | Respirable fraction. |
| Titanium Dioxide (CAS 13463-67-7) | TWA | | 10 |) mg/m3 | |
| US. NIOSH: Pocket Guide | to Chemical Hazards | | | | |
| Components | Туре | | V | alue | Form |
| 1-methoxy-2-propanol (CA | S STEL | | 54 | 40 mg/m3 | |
| 107-98-2) | | | | | |
| | | | | 50 ppm | |
| | TWA | | | 60 mg/m3 | |
| | T1444 | | | 00 ppm | |
| Aromatic Hydrocarbon Solvents (CAS 64742-95-6 | TWA | | 40 | 00 mg/m3 | |
| 301Verits (CA3 04742-93-0 |) | | 1(| 00 ppm | |
| Barium Sulfate (CAS | TWA | | | mg/m3 | Respirable. |
| 7727-43-7) | . **/ | | O | g, | |
| · | | | | 0 mg/m3 | Total |
| Carbon Black (CAS | TWA | | 0. | 1 mg/m3 | |
| 1333-86-4) Ethyl Benzene (CAS | STEL | | 54 | 45 mg/m3 | |
| 100-41-4) | | | 47 | 25 nnm | |
| | TWA | | | 25 ppm 35 mg/m3 | |
| | IWA | | | 35 mg/m3 00 ppm | |
| Talc (CAS 14807-96-6) | TWA | | | mg/m3 | Respirable. |
| , | IVVA | | 2 | mg/mo | i tespirable. |
| ogical limit values | | | | | |
| ACGIH Biological Exposu Components | re Indices Value | Determinant | Specimen | Sampling | Time |
| Ethyl Benzene (CAS 100-41-4) | 0.15 g/g | Sum of mandelic acid | Creatinine in urine | * | |
| , | | and | | | |
| | | phenylglyoxylic | | | |

 $[\]ensuremath{^{\star}}$ - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

1-methoxy-2-propanol (CAS 107-98-2)

Can be absorbed through the skin.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment

Eye/face protection Face shield is recommended. Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance Liquid.
Physical state Liquid.
Form Liquid.

Color Grays and Buff

Odor Slight.

Odor threshold Not available.

PH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling

range

392 °F (200 °C) estimated

Flash point > 102.0 °F (> 38.9 °C)

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 0.13 hPa estimated

Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Density 1.67 g/cm3 **Explosive properties** Not explosive.

Flammability class Combustible II estimated

Oxidizing properties Not oxidizing.

Specific gravity 1.67

VOC 0.76 lb/gal Mixed components

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Chemical stability Material is stable under normal conditions. Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Strong oxidizing agents. Incompatible materials

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction.

Dermatitis. Rash.

Information on toxicological effects

Not known. Acute toxicity

Components **Species Test Results**

Ethyl Benzene (CAS 100-41-4)

Acute Oral

LD50 Rat

3500 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

Causes serious eye irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Risk of cancer cannot be excluded with prolonged exposure. Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

Carbon Black (CAS 1333-86-4) 2B Possibly carcinogenic to humans. Ethyl Benzene (CAS 100-41-4) 2B Possibly carcinogenic to humans. 2B Possibly carcinogenic to humans. Talc (CAS 14807-96-6)

3 Not classifiable as to carcinogenicity to humans.

Titanium Dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

^{*} Estimates for product may be based on additional component data not shown.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Not an aspiration hazard. **Aspiration hazard**

Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects. **Chronic effects**

12. Ecological information

Toxic to aquatic life with long lasting effects. **Ecotoxicity**

Persistence and degradability Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Ethyl Benzene 3.15

No data available. Mobility in soil

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow **Disposal instructions**

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN1263 **UN number** Paint

UN proper shipping name Transport hazard class(es)

3 Class Subsidiary risk Label(s) 3 Ш Packing group

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

B1, B52, IB3, T2, TP1, TP29 Special provisions

150 Packaging exceptions Packaging non bulk 173 Packaging bulk 242

IATA

UN1263 **UN number UN proper shipping name** Paint

Transport hazard class(es)

Class 3 Subsidiary risk Ш Packing group **Environmental hazards** No.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Allowed with restrictions. Cargo aircraft only

IMDG

UN number UN1263

UN proper shipping name Paint, MARINE POLLUTANT

Transport hazard class(es)

Class 3
Subsidiary risk Packing group |||

Environmental hazards

Marine pollutant

 $\begin{tabular}{ll} \mbox{Marine pollutant} & \mbox{Yes} \\ \mbox{EmS} & \mbox{F-E, S-E} \\ \end{tabular}$

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Not established.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

DOT



IATA; IMDG



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

1-methoxy-2-propanol (CAS 107-98-2)

Barium Sulfate (CAS 7727-43-7)

Ethyl Benzene (CAS 100-41-4)

Zinc Phosphate (CAS 7779-90-0)

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration

Ethyl Benzene (CAS 100-41-4) % 0.1
Zinc Phosphate (CAS 7779-90-0) % 1.0 N982

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Ethyl Benzene (CAS 100-41-4) Listed.

Zinc Phosphate (CAS 7779-90-0) Listed. N982

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

SARA 313 (TRI reporting)

| Chemical name | CAS number | % by wt. |
|----------------|------------|----------|
| Ethyl Benzene | 100-41-4 | 0.1 - 1 |
| Zinc Phosphate | 7779-90-0 | 5 - 10 |

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Ethyl Benzene (CAS 100-41-4)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

WARNING: This product contains a chemical known to the State of California to cause cancer and

birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Carbon Black (CAS 1333-86-4)
Ethyl Benzene (CAS 100-41-4)
Listed: February 21, 2003
Listed: June 11, 2004
Listed: September 2, 2011

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Toluene (CAS 108-88-3) Listed: January 1, 1991

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

1-methoxy-2-propanol (CAS 107-98-2)

Aromatic Hydrocarbon Solvents (CAS 64742-95-6)

Carbon Black (CAS 1333-86-4) Ethyl Benzene (CAS 100-41-4) Talc (CAS 14807-96-6)

Titanium Dioxide (CAS 13463-67-7)

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|----------------------|--|------------------------|
| Australia | Australian Inventory of Chemical Substances (AICS) | No |
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | Yes |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | Yes |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | No |

Country(s) or region Inventory name On inventory (yes/no)*

Korea Existing Chemicals List (ECL) No
New Zealand New Zealand Inventory Yes

Philippines Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

 Issue date
 05-29-2015

 Revision date
 03-02-2017

Version # 02

HMIS® ratings Health: 2

Flammability: 2 Physical hazard: 0 Personal protection: B

NFPA ratings Health: 2

Flammability: 2 Instability: 0

Disclaimer ITW Engineered Polymers cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently

available.

Revision information This document has undergone significant changes and should be reviewed in its entirety.

Material name: American Safety Technologies MS-11CZ Buff - Part A MS709R Version #: 02 Revision date: 03-02-2017 Issue date: 05-29-2015

No