



TECHNICAL DATA SHEET – ULTRACHROME 1552

Revised: 05/2018

PRODUCT DESCRIPTION

A crosslinker used as an additive to Ultrachrome 452 when there is a requirement for increased adhesion. This would typically arise when the Ultrachrome 452 is being applied onto old 5410 or there is a time delay in production between Ultrathane 5410 and Ultrachrome 452 overcoating.

FEATURES

Specifically for use with Ultrachrome 452 as a crosslinker to increase adhesion.

RECOMMENDED USES: Only to be used with Ultrachrome 452.

TYPICAL PROPERTIES

COLOR	99% ± 1
FLASH POINT (°C)	0 lbs/gal (0 g/L)
% SOLIDS BY VOLUME	1604 ft ² /gal @ 1 mil (3.8 m ² /gal @ 1.0mm)
USAGE	30-100 mils

PACKAGE SIZE: 13fl.oz (384ml)

APPLICATION INFORMATION

Ultrachrome 1552 is added to Ultrachrome 452 and then mixed thoroughly before the material is then sprayed in accordance with Ultrachrome 452 TDS.

SHELF LIFE

A shelf life of 12 months from date of shipment can be expected when stored in dry conditions at room temperature (~22°C) in their original containers.

PRECAUTIONS

For complete safety and handling information, please refer to Material Safety Data Sheets prior to using this product.

ULTRACHROME 1552



TECHNICAL DATA SHEET – ULTRACHROME 1552

ITW Polymers Sealants North America, Inc. warrants its products to be free from defects in material and workmanship. ITW Polymers Sealants North America, Inc.'s sole obligation and Buyer's exclusive remedy in connection with the products shall be limited, at ITW Polymers Sealants North America, Inc.'s option, to either replacement of products not conforming to this warranty or credit to Buyer's account in the invoiced amount of the nonconforming products. Any claim under this Warranty must be made by Buyer to ITW Polymers Sealants North America, Inc. in writing within five days of Buyer's discovery of the claimed defect, but in no event later than the expiration of the applicable shelf life, or one year from the delivery date, whichever is earlier. Buyer's failure to notify ITW Polymers Sealants North America, Inc. of such nonconformance as required herein shall bar Buyer from recovery under this warranty.

ITW Polymers Sealants North America, Inc. makes no other warranties concerning this product. No other warranties, either expressed or implied, or statutory, such as warranties of merchantability or fitness for a particular purpose, shall apply. In no event shall ITW Polymers Sealants North America, Inc. be liable for consequential or incidental damages.

Any recommendation or suggestion relating to the use of the products made by ITW Polymers Sealants North America, Inc., whether in its technical literature, or in response to specific inquiry, or otherwise, is based on data believed to be reliable; however, the products and information are intended for use by Buyers having requisite skill and know-how in the industry, and therefore it is for the Buyer to satisfy itself of the suitability of the products for its own particular use, and it shall be deemed that Buyer has done so, at its sole discretion and risk. Variation in environment changes in procedures of use, or extrapolation of data may cause unsatisfactory results. ITW Polymers Sealants North America, Inc. cannot guarantee that color will conform to sample, if provided.

ITW POLYMERS SEALANTS NORTH AMERICA, INC.

111 S. Nursery Road, Irving, TX 75060 • Tel: +1 972-438-9111

Fax +1 972-554-3939 • info@itwsealants.com • futuracoatings.com

ITW Polymers Sealants North America